

**Safety data sheet (English translation without any country-specific legislation)
according to 1907/2006/EC, Article 31**

Printing date 13.09.2023

Rev. 1

Revision: 13.09.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
 - Trade name: **LITOSIL COLOR**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** Adhesive/ sealant
 - Product category PC1 Adhesives, sealants
 - Application of the substance / the mixture
Sealant for bathroom fixtures and tiles based on polysiloxanes and acetic crosslinkers.
- **1.3 Details of the supplier of the safety data sheet**
 - Manufacturer/Supplier:
LITOKOL S.p.A.
Via G.Falcone, 13/1
42048 Rubiera (RE) - ITALY
Tel. +39 0522 626391 - Fax. +39 0522 620150
 - Further information obtainable from: LITOKOL S.p.A. - Email: productsafety@litokol.it
- **1.4 Emergency telephone number:**
ITALY - POISONS CENTRES (24h / 365d):
 - Milano - Azienda Ospedaliera Niguarda Ca' Granda - Tel. +39 02 66101029
 - Pavia - Centro Nazionale d'Informazione Tossicologica - IRCCS Fondazione Salvatore Maugeri Clinica del Lavoro e della riabilitazione - Tel. +39 0382 24444
 - Firenze - Azienda Ospedaliera Universitaria "Careggi" U.O. Tossicologia Medica - Tel. +39 055 7947819
 - Bergamo - Azienda Ospedaliera "Papa Giovanni XXIII", tossicologia clinica - Tel. +39 800 883300
 - Roma - CAV Policlinico "Umberto I", PRGM tossicologia d'urgenza - Tel. +39 06 49978000
 - Roma - CAV del Policlinico "Agostino Gemelli", Servizio di tossicologia clinica - Tel. +39 06 3054343
 - Roma - CAV "Ospedale Pediatrico Bambino Gesù", dipartimento emergenza e accettazione DEA - Tel. +39 06 68593726
 - Foggia - Azienda Ospedaliera Universitaria riuniti, Foggia - Tel. +39 800 183459
 - Napoli - Azienda Ospedaliera "Antonio Cardarelli", III Servizio di anestesia e rianimazione - Tel. +39 081 5453333
 - Verona - CAV dell'Azienda ospedaliera integrata (AOUI) di Verona sede di Borgo Trento - Tel. +39 800 011858

LITOKOL S.p.A.
Technical support: Tel. +39 0522 622852 (Monday - Friday: 8.30-12.30 AM , 2.00-6.00 PM)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
 - Classification according to Regulation (EC) No 1272/2008
The product is not classified, according to the CLP regulation.
- **2.2 Label elements**
 - Labelling according to Regulation (EC) No 1272/2008 Void
 - Hazard pictograms Void
 - Signal word Void
 - Hazard statements Void
 - Additional information:
EUH208 Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.
EUH210 Safety data sheet available on request.
- **2.3 Other hazards**
 - Results of PBT and vPvB assessment
 - PBT: Not applicable.
 - vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
 - Description: Mixture consisting of the following components:

· Dangerous components:		
Reg.nr.: 01-2119552497-29-XXXX	Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics Alternative CAS number: 1335203-18-3 ⚠ Asp. Tox. 1, H304 Note: N	≥5-≤10%
CAS: 17689-77-9 EINECS: 241-677-4 Reg.nr.: 01-2119881778-15-XXXX	ethyltriacetoxysilane ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302, EUH014	≥2.5-<3%

(Contd. on page 2)

**Safety data sheet (English translation without any country-specific legislation)
according to 1907/2006/EC, Article 31**

Printing date 13.09.2023

Rev. 1

Revision: 13.09.2023

Trade name: LITOSIL COLOR

	Ethyl- and methylacetoxysilanes oligomers (non-isolatable in situ generated adduct)	(Contd. of page 1) ≥1.5-<2%
	⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318	
CAS: 64359-81-5 EINECS: 264-843-8 Index number: 613-335-00-8	4,5-dichloro-2-octyl-2H-isothiazol-3-one ⚠ Acute Tox. 2, H330; ⚠ Skin Corr. 1, H314; Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); ⚠ Acute Tox. 4, H302; Skin Sens. 1A, H317, EUH071 ATE: LD50 oral: 567 mg/kg LC50 / 4h inhalative: 0.16 mg/l Specific concentration limits: Skin Irrit. 2; H315: C ≥ 0.025 % Eye Irrit. 2; H319: C ≥ 0.025 % Skin Sens. 1A; H317: C ≥ 0.0015 %	≥0.00025-<0.0015%

Additional information:

For the wording of the listed hazard phrases refer to section 16.

If no ATE values are present, refer to LD/LC50 values in section 11.

During cross-linking, it develops ACETIC ACID (CAS 64-19-7, EINECS 200-580-7, INDEX 607-002-00-6) by hydrolysis of acetoxysilanes.

Flam. Liq. 3, H226; Skin Corr. 1A, H314; Note: B

Specific concentration limits:

Skin Corr. 1A, H314: C ≥ 90 %

Skin Corr. 1B, H314: 25 % ≤ C < 90 %

Skin Irrit. 2, H315: 10 % ≤ C < 25 %

Eye Irrit. 2, H319: 10 % ≤ C < 25 %

SECTION 4: First aid measures**4.1 Description of first aid measures**· **General information:** Take off contaminated clothing and wash it before reuse.· **After inhalation:** Supply fresh air; consult doctor in case of complaints.· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

Generally the product does not irritate the skin.

· **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.· **After swallowing:**

Do not induce vomiting; call for medical help immediately.

Rinse out mouth and then drink plenty of water.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**· **Suitable extinguishing agents:**

Use fire extinguishing methods suitable to surrounding conditions.

CO₂, powder or water spray. Fight larger fires with water spray.**5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters· **Protective equipment:** Do not inhale explosion gases or combustion gases.· **Additional information**

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Particular danger of slipping on leaked/spilled product.

Ensure adequate ventilation

· **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

**Safety data sheet (English translation without any country-specific legislation)
according to 1907/2006/EC, Article 31**

Printing date 13.09.2023

Rev. 1

Revision: 13.09.2023

Trade name: LITOSIL COLOR

(Contd. of page 2)

- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Pick up mechanically.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep away from heat and direct sunlight.
- **Information about fire - and explosion protection:**
The product is not flammable.
No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
 - **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Keep receptacles tightly sealed.
 - **Information about storage in one common storage facility:**
Store away from water.
Do not store together with oxidising and acidic materials.
Do not store together with alkalis (caustic solutions).
 - **Further information about storage conditions:**
Protect from humidity and water.
Store receptacle in a well ventilated area.
Protect from frost.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

CAS: 17689-77-9 ethyltriacetoxysilane

Oral	DNEL / Long term exposure - Systemic effects	5.7 mg/Kg bw/d (general population)
Dermal	DNEL / Long term exposure - Systemic effects	5.7 mg/Kg bw/d (general population)
Inhalative		11.39 mg/Kg bw/d (workers)
	DNEL / Long term exposure - Systemic effects	19.81 mg/m ³ (general population)
		80.33 mg/m ³ (workers)
	DNEL / Long term exposure - Local effects	6.5 mg/m ³ (general population)
		32.5 mg/m ³ (workers)
	DNEL / Short term exposure - Local effects	32.5 mg/m ³ (workers)

· PNECs

CAS: 17689-77-9 ethyltriacetoxysilane

PNEC / aqua	0.023-0.2 mg/l (freshwater)
	1.7 mg/l (Intermittent releases (freshwater))
	0.0023-0.02 mg/l (marine water)
PNEC / sediment	0.023-0.74 mg/Kg dw (freshwater)
	0.0023-0.074 mg/Kg dw (marine water)
PNEC / soil	0.0064-0.031 mg/Kg dw
PNEC / STP	1-10.637 mg/l (sewage treatment plant)

(Contd. on page 4)

EU

**Safety data sheet (English translation without any country-specific legislation)
according to 1907/2006/EC, Article 31**

Printing date 13.09.2023

Rev. 1

Revision: 13.09.2023

Trade name: LITOSIL COLOR

(Contd. of page 3)

Regulatory information**Additional Occupational Exposure Limit Values for possible hazards during processing:****CAS: 64-19-7 acetic acid**

IOELV (EU)	Short-term value: 50 mg/m ³ , 20 ppm Long-term value: 25 mg/m ³ , 10 ppm
AGW (Germany)	Long-term value: 25 mg/m ³ , 10 ppm 2(l);DFG, EU, Y
VLEP (France)	Short-term value: 50 mg/m ³ , 20 ppm Long-term value: 25 mg/m ³ , 10 ppm
WEL (Great Britain)	Short-term value: 50 mg/m ³ , 20 ppm Long-term value: 25 mg/m ³ , 10 ppm
TWA (Italy)	Short-term value: 37 mg/m ³ , 15 ppm Long-term value: 25 mg/m ³ , 10 ppm
VL (Italy)	Short-term value: 50 mg/m ³ , 20 ppm Long-term value: 25 mg/m ³ , 10 ppm
PEL (USA)	Long-term value: 25 mg/m ³ , 10 ppm
REL (USA)	Short-term value: 37 mg/m ³ , 15 ppm Long-term value: 25 mg/m ³ , 10 ppm
TLV (USA)	Short-term value: 15 ppm Long-term value: 10 ppm

Additional information:

IOELV (EU): (EU) 2019/1831
 AGW (Germany): TRGS 900
 VLEP (France): ED 1487 05.2021
 WEL (Great Britain): EH40/2020
 TWA (Italy): Valori Limite di Soglia (ACGIH)
 VL (Italy): D.lgs. n. 81/2008
 PEL (USA): Guide to Occupational Exposure Values (OSHA PELs)
 REL (USA): Guide to Occupational Exposure Values (NIOSH RELs)
 TLV (USA): Guide to Occupational Exposure Values (TLV)
 The lists valid during the making were used as basis.

8.2 Exposure controls

- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.
 Wash hands before breaks and at the end of work.
 Do not eat or drink while working.
 Avoid contact with the eyes.

Respiratory protection:

Not necessary if room is well-ventilated.



Use suitable respiratory protective device in case of insufficient ventilation.

Short term filter device:

Filter A
 Filter ABEK

Hand protection

Preventive skin protection by use of:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Butyl rubber, BR
 Nitrile rubber, NBR

- **Eye/face protection** Goggles recommended.

(Contd. on page 5)

**Safety data sheet (English translation without any country-specific legislation)
according to 1907/2006/EC, Article 31**

Printing date 13.09.2023

Rev. 1

Revision: 13.09.2023

Trade name: LITOSIL COLOR

(Contd. of page 4)

· **Body protection:** Light weight protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state	Fluid
· Colour:	Different according to colouring
· Odour:	Pungent
	Vinegar
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	Undetermined.
· Flammability	Non-flammable mixture
· Lower and upper explosion limit	
· Lower:	4 Vol % (CAS: 64-19-7 liberated acetic acid)
· Upper:	17 Vol % (CAS: 64-19-7 liberated acetic acid)
· Flash point:	>150 °C
· Auto-ignition temperature:	400 °C
· Decomposition temperature:	Not applicable. Mixture is not self-reactive, does not contain organic peroxide and does not decompose under foreseen conditions of use
· pH	Not applicable. Mixture reacts with water.
· Viscosity:	
· Kinematic viscosity	Not applicable. Thixotropic behavior
· Solubility	
· water:	Insoluble.
· Partition coefficient n-octanol/water (log value)	Not applicable.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	1-1.03 g/cm ³
· Relative gas density	>1
· Particle characteristics	Fluid

· 9.2 Other information

· Appearance:	
· Form:	Pasty
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Solvent content:	
· VOC (EC)	0.00 %
· Change in condition	
· Evaporation rate	Not determined.

· Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void

(Contd. on page 6)

EU

**Safety data sheet (English translation without any country-specific legislation)
according to 1907/2006/EC, Article 31**

Printing date 13.09.2023

Rev. 1

Revision: 13.09.2023

Trade name: LITOSIL COLOR

(Contd. of page 5)

· Desensitised explosives

Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No dangerous reactions known.
- **10.2 Chemical stability**
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**
 - Reacts violently with water.
 - Reacts with strong acids and oxidising agents.
 - Reacts with strong bases
- **10.4 Conditions to avoid**
 - Keep ignition sources away - Do not smoke.
 - Protect from humidity and water.
- **10.5 Incompatible materials:**
 - Reacts with acids, alkalis and oxidising agents.
 - Store away from water.
- **10.6 Hazardous decomposition products:**
 - Ethanoic acid
 - Formation of toxic gases is possible during heating or in case of fire.
 - Small quantities of formaldehyde may be formed

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
 - **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Oral	LD50	48,829-58,400 mg/kg (rat)
------	------	---------------------------

CAS: 17689-77-9 ethyltriacetoxysilane

Oral	LD50	1,460 mg/kg (rat) (OECD TG 401: Acute Oral Toxicity)
------	------	--

CAS: 64359-81-5 4,5-dichloro-2-octyl-2H-isothiazol-3-one

Oral	LD50	567 mg/kg (ATE)
Inhalative	LC50 / 4h	0.16 mg/l (ATE)

CAS: 64-19-7 acetic acid

Oral	LD50	3,310 mg/kg (rat)
------	------	-------------------

· Skin corrosion/irritation

In vivo skin irritation data are available for a preparation containing a mixture of approximately 5% (total) triacetoxymethylsilane and the related substance triacetoxymethylsilane (Bayer AG, 1986). This preparation is similar to products marketed for professional and consumer sealant applications. Minor, reversible effects were observed: the preparation is not irritant to skin according to EU criteria -> Not irritating (rabbit) - OECD Guideline 404: Acute Dermal Irritation/Corrosion

· Serious eye damage/irritation

In vivo eye irritation data are available for a preparation containing a mixture of approximately 5% (total) triacetoxymethylsilane and the related substance triacetoxymethylsilane (Bayer AG, 1986). This preparation is similar to products marketed for professional and consumer sealant applications. Minor, reversible effects were observed: the preparation is not irritant to eyes according to EU criteria -> Not irritating (rabbit) - OECD Guideline 405: Acute Eye Irritation/Corrosion

- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

- **Carcinogenicity** Based on available data, the classification criteria are not met.

- **Reproductive toxicity** Based on available data, the classification criteria are not met.

- **STOT-single exposure** Based on available data, the classification criteria are not met.

- **STOT-repeated exposure** Based on available data, the classification criteria are not met.

- **Aspiration hazard** Based on available data, the classification criteria are not met.

(Contd. on page 7)

EU

**Safety data sheet (English translation without any country-specific legislation)
according to 1907/2006/EC, Article 31**

Printing date 13.09.2023

Rev. 1

Revision: 13.09.2023

Trade name: LITOSIL COLOR

(Contd. of page 6)

· **11.2 Information on other hazards**· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information· **12.1 Toxicity**· **Aquatic toxicity:****CAS: 64359-81-5 4,5-dichloro-2-octyl-2H-isothiazol-3-one**

EC50 / 48h 0.0057 mg/l (crustacea - Daphnia magna)

LC50 / 96h 0.0027 mg/l (fish - Oncorhynchus mykiss) (OECD TG 203: Fish, Acute Toxicity Test)

EC50 / 72h 0.048 mg/l (algae - Pseudokirchneriella subcapitata) (OECD TG 201: Alga, Growth Inhibition Test)

NOEC 0.00056 mg/l /97 d (fish - Oncorhynchus mykiss)

NOEC / 21d 0.00063 mg/l (crustacea - Daphnia magna)

· **12.2 Persistence and degradability** Silicone content: non biodegradable.· **12.3 Bioaccumulative potential** Does not accumulate in organisms· **12.4 Mobility in soil** No further relevant information available.· **12.5 Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.· **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.· **12.7 Other adverse effects**· **Additional ecological information:**· **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations· **13.1 Waste treatment methods**· **Recommendation**

Disposal must be made according to official regulations.

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

· **Uncleaned packaging:**· **Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information**· **14.1 UN number or ID number**· **ADR/RID/ADN, IMDG, IATA**

Void

· **14.2 UN proper shipping name**· **ADR/RID/ADN, IMDG, IATA**

Void

· **14.3 Transport hazard class(es)**· **ADR/RID/ADN, ADN, IMDG, IATA**· **Class**

Void

· **14.4 Packing group**· **ADR/RID/ADN, IMDG, IATA**

Void

· **14.5 Environmental hazards:**· **Marine pollutant:**

No

· **14.6 Special precautions for user**

Not applicable.

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· **UN "Model Regulation":**

Void

(Contd. on page 8)

**Safety data sheet (English translation without any country-specific legislation)
according to 1907/2006/EC, Article 31**

Printing date 13.09.2023

Rev. 1

Revision: 13.09.2023

Trade name: LITOSIL COLOR

(Contd. of page 7)

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
Regulation (EC) No 1907/2006 (REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals)
Regulation (EC) No 1272/2008 (CLP - Classification, Labelling and Packaging of substances and mixtures)
Compilation of Safety Data Sheet: Reg.UE n. 878/2020 (amending Reg.EC n.1907/2006, Annex II)

- **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

- **REGULATION (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

- **REGULATION (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

- **REGULATION (EU) 2019/1148**

- **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

- **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H330 Fatal if inhaled.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- EUH014 Reacts violently with water.
- EUH071 Corrosive to the respiratory tract.

- **Contact:** LITOKOL S.p.A.

- **Abbreviations and acronyms:**

- REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
- CLP: Classification, Labelling and Packaging
- TLV: Threshold Limit Value
- TLV-TWA: Threshold Limit Value - Time Weighted Average
- TLV-STEL: Threshold Limit Value - Short Term Exposure Limit
- PEL: Permissible Exposure Limits (Limiti di esposizione consentiti)
- REL: Recommended Exposure Limits (Limiti di esposizione raccomandati)
- IOELV: Indicative Occupational Exposure Limit Value
- WEELS: Workplace Environmental Exposure Limits (Limiti di esposizione ambientale sul posto di lavoro)
- BEL: Biological Exposure Indices
- LC50: Lethal Concentration, 50 percent
- EC50: Effective Concentration, 50 percent
- ErC50: Effective Concentration, 50 percent, reduction of growth rate
- NOEC: No-Observed Effect Concentration
- NOELR: No-Observed Effect Loading Rate
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Acute Tox. 4: Acute toxicity – Category 4
- Acute Tox. 2: Acute toxicity – Category 2

(Contd. on page 9)

EU

**Safety data sheet (English translation without any country-specific legislation)
according to 1907/2006/EC, Article 31**

Printing date 13.09.2023

Rev. 1

Revision: 13.09.2023

Trade name: LITOSIL COLOR

(Contd. of page 8)

*Skin Corr. 1: Skin corrosion/irritation – Category 1**Skin Corr. 1B: Skin corrosion/irritation – Category 1B**Eye Dam. 1: Serious eye damage/eye irritation – Category 1**Skin Sens. 1A: Skin sensitisation – Category 1A**Asp. Tox. 1: Aspiration hazard – Category 1**Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1**Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1*

EU